



Product: Double Sided Stereo Mount – 380 Mic

Code: D011

Product Description

A calibrated thickness polyester cloth carrier with a solvent-based rubber adhesive.

Features

- The rubber adhesive system provides high adhesion performances, but can also be repositioned.
- High dimensional stability carrier.

Applications

- Ideal for cardboard printing in post-print and relevant pre-mounting operations of rubber cliché/photopolymer plates applied on PET/PP film sheets or directly on steel cylinders.
- Recommended for medium and high thickness grades of photopolymer plates.

Technical Data

Liner	Siliconized glassine liner – Havana
Carrier	White PET Cloth
Adhesive	Solvent based rubber
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	30°C
Temperature Resistance	80°C
Shear Strength (BS68-AFERA5012)	5 hours
180° Peel Adhesion (BS34-AFERA5001)	20N/25mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ISO13934-1/00)*	380N
Elongation (ISO13934-1/00)*	25.3%
Initial Tack (BS12-PSTC-6)*	1cm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Store between 15° and 27°C and relative humidity < 60% and use within 12 months