



**Product:** Double Sided Foam 1.5mm

**Code:** D037

### Product Description

Premium grade white polyethylene foam coated on both sides with a solvent adhesive.

### Features

- High initial tack.
- High temperature resistance.
- Long life adhesive.

### Applications

- Ideally suited for many different mounting applications, number plates, name plates and signs.
- Light weight binding and attachment of uneven or rough surfaces.
- Good adhesion to many surfaces coupled to excellent sheer strength.

### Technical Data

Liner	Siliconized polyethylene film – Red
Carrier	Polyethylene foam
Adhesive	Solvent based acrylic (high tack)
Film Thickness	1.5mm
Adhesive Thickness	N/A
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	16°-30°C
Temperature Resistance	110°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥9N/25mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	>20N/25mm
Elongation (ASTM D 3759)*	200%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry and clean environment – 12 months