



Product: Double Sided Foam 3mm

Code: D038

Product Description

Premium grade white polyethylene foam coated on both sides with a solvent adhesive.

Features

- High initial tack.
- High temperature resistance.
- Long life adhesive.

Applications

- Ideally suited for many different mounting applications, number plates, name plates and signs.
- Light weight binding and attachment of uneven or rough surfaces.
- Good adhesion to many surfaces coupled to excellent sheer strength.

Technical Data

Liner	Siliconized polyethylene film – Red
Carrier	Polyethylene foam
Adhesive	Solvent based acrylic (high tack)
Film Thickness	3mm
Adhesive Thickness	N/A
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	16°-30°C
Temperature Resistance	110°C
Sheer Strength	1000g, 6.4cm ² , 2880min +
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥25N/25mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	N/A
Elongation (ASTM D 3759)*	N/A
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry and clean environment – 12 months