



Product: Double Sided Polyprop RDA

Code: D039

Product Description

An OPP material, coated on both sides with a solvent based acrylic adhesive.

Features

- High initial tack.
- High temperature resistance.
- Long life adhesive.
- Good transparency.

Applications

- Ideally suited for plastic and metal nameplate mounting.
- Print finishing of cosmetic packaging, joining of leather, PVC films, fabric jointing, high value PE and Paper Bags
- Felt / foam bonding and laminating.

Technical Data

Liner	PE paper – brown
Carrier	OPP - clear
Adhesive	Solvent based acrylic
Film Thickness	90 Micron
Adhesive Thickness	80g/m ²
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	8° - 38°C
Temperature Resistance	-15° to 90°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥11N/25mm
Holding Power (ASTM D 3654)*	≥120mins
Tensile Strength (ASTM D 3759)*	20N/cm
Elongation (ASTM D 3759)*	17%
Initial Tack (JIS Z0237)*	≤100mm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months