



JOHANNESBURG - Tel: 011 975 0530 CAPE TOWN - Tel: 021 703 2340



JOHANNESBURG (Head Office) 10 Forge Road, Spartan, Kempton Park CAPE TOWN 32 12th Street, Elsies River



Company Reg. No. : 1983/002184/07 VAT No. : 4440192302



Code: E001

www.easitape.co.za

Product: PVC Floormarking Tape

Product Description

A thick, high performance, conformable PVC tape with a synthetic acrylic adhesive. Available in red, yellow, blue, green, white and black as well as black/yellow and white/red stripes

Features

- The strong thick, yet conformable carrier and excellent adhesion provide superior performance, and long life.
- It is moisture resistant, easily cleaned and highly abrasion resistant, and it gives clean removal off most surfaces.

Applications

- Ideally suited to colour coding and demarcation of factory and other floor areas.
- Extremely versatile with multiple uses.

Technical Data

Liner	N/A
Carrier	PVC
Adhesive	Rubber
Film Thickness	140 Micron
Adhesive Thickness	N/A
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	15° to 80°C
Temperature Resistance	80°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	30N/100mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	300N/100mm
Elongation (ASTM D 3759)*	80%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Dry ambient conditions – 24 months