



Product: Yellow Protection Film 90 Mic

Code: E016

Product Description

A yellow and white co-extruded polyethylene protective UV film.

Features

- Protects surfaces from abrasion, corrosion, dirt and contamination during storage or in production.
- Stable adhesion ensures edges do not lift in wind but allows clean removal even after sunlight exposure.
- Strong film properties resist tearing and the solvent acrylic adhesive ensures good moisture resistance, and good adhesion even to textured surfaces.
- Exterior ageing for periods up to 6 months.

Applications

- Temporary protection of many metals, plastics, glass and painted surfaces.
- Protection against dirt and damage during processing, storage and mounting.

Technical Data

Liner	N/A
Carrier	Yellow (outside) / White (inside) Co-Ex Polyethylene
Adhesive	Acrylic
Film Thickness	85 Micron
Adhesive Thickness	5 Micron
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	10° to 40°C
Temperature Resistance	75°C (maximum)
Shear Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	700 +/- 60g/25mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	N/A
Elongation (ASTM D 3759)*	>180%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Room temperature < 40°C; storage above 40°C may cause blocking of the rolls, therefore outside storage and direct sunlight should be avoided. Storage time max. 6 months after date of production



JOHANNESBURG - Tel: 011 975 0530
CAPE TOWN - Tel: 021 703 2340



JOHANNESBURG (Head Office)
10 Forge Road, Spartan, Kempton Park
CAPE TOWN
32 12th Street, Elsies River



Company Reg. No. : 1983/002184/07
VAT No. : 4440192302



www.easitape.co.za