



**Product:** Tamper Evident Packaging Tape

**Code:** TE001/2

## Product Description

A high strength polyester film with a modified solvent based acrylic adhesive and a full transfer of the VOID message when peeled away. Available in red and blue.

## Features

- High initial tack. (ultra-aggressive quick bond)
- High temperature resistance and long life adhesive.
- Designed to maintain the integrity of your shipments, providing both the sender and receiver with the security of knowing that the shipment has not been tampered with.
- Carrier is a high strength polyester film with low elongation, which lends itself to both manual and machine applied taping applications.

## Applications

- Suitable to be used on a wide range of substrates (paper, board, recycled paper/board, polyethylene, glass and stretch films)
- Typically used for confidential document pouches, high value products, medical and pharmaceutical products.

## Technical Data

Liner	N/A
Carrier	Self-wound Polyester
Adhesive	Solvent Based Acrylic
Film Thickness	30 Micron
Adhesive Thickness	20 Micron
Total Thickness Allowance (Variance)	+/- 5%
Application Temperature	10°-30°C
Temperature Resistance	190°C
180° Peel Adhesion (ASTM D 3330)* (Steel)	13N/cm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	>40N/cm
Elongation (ASTM D 3759)*	5%
Initial Tack (JIS Z0237)*	≤50mm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area away from direct sunlight – 12 months