

**Product:** Tamper Evident Label Grade

**Code:** TE004-10

### Product Description

A polyester film with a modified solvent based acrylic adhesive and an option of VOID messages when peeled away: no transfer, partial and full transfer. Available in: Matt Silver, Red, Blue, White and Mirror Silver.

### Features

- High initial tack. (ultra-aggressive quick bond)
- High temperature resistance and long life adhesive.
- Designed to maintain the integrity of your shipments, providing both the sender and receiver with the security of knowing that the shipment has not been tampered with.
- Suitable for flexographic printing, UV relief printing, laser printing and thermal ink processing mode as well as die-cutting.

### Applications

- Suitable to be used on a wide range of substrates (paper, board, recycled paper/board, polyethylene, glass and stretch films)
- Typically used for confidential document pouches, high value products, medical and pharmaceutical products.

### Technical Data

Liner	Glassine Paper (80g)
Carrier	Polyester
Adhesive	Solvent Based Acrylic
Film Thickness	25 Micron
Adhesive Thickness	15 Micron
Total Thickness Allowance (Variance)	+/- 5%
Application Temperature	10°-30°C
Temperature Resistance	190°C
180° Peel Adhesion (ASTM D 3330)* (Steel)	13N/cm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	> 40N/cm
Elongation (ASTM D 3759)*	5%
Initial Tack (JIS Z0237)*	≤50mm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area away from direct sunlight – 12 months